

Report ID: 107478

Report Information

Submitting Organisation: 00121120: Zintec Corrosion Solutions **Account:** 142045: Zintec Corrosion Solutions

AWQC Reference: 142045-2012-CSR-1 : Prod Test: Zinga LGF

Project Reference : PT-1857

Product Designation: Zinga

Composition of Product: 96% Zinc in Dry Film (see MSDS and Technical Data Sheet for additional information).

Product Manufacturer : Zingametall, BELGIUM.

Use of Product: In-Line/Protective Coating of Steel Assets.

Sample Selection: As provided by the submitting organisation.

Testing Requested: AS/NZS 4020:2005 TESTING OF PRODUCTS FOR USE IN CONTACT WITH

DRINKING WATER

Product Type: Composite

Samples: Samples were prepared and controlled as described in Appendix A of AS/NZS

4020:2005

Extracts: Extracts were prepared as described in Appendix C, D, E, F, G, H.

Project Completion Date: 23-Aug-2012

Project Comment: The results presented herein demonstrate compliance to AS/NZS 4020 for Zinga,

exposed at an area to volume ratio up to 1000 mm2/L at 20°C ± 2°C.

PLEASE NOTE THAT THIS REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL

THE RESULTS STATED IN THIS REPORT RELATE TO THE SAMPLE OF THE PRODUCT SUBMITTED FOR TESTING. ANY CHANGES IN THE MATERIAL FORMULATION, PROCESS OF MANUFACTURE, THE METHOD OF APPLICATION, OR THE SURFACE AREA-TO-VOLUME RATIO IN THE END USE, COULD AFFECT THE SUITABILITY OF THE PRODUCT FOR USE IN CONTACT WITH DRINKING WATER

M Marion.

Michael Glasson APPROVED SIGNATORY



Australian Water Quality Centre

FINAL REPORT

Report ID: 107478

Summary of Results

APPENDIX	RESULTS		
C — Taste of Water Extract	Passed at an exposure of 1000 mm2/L.		
D — Appearance of Water Extract	Passed at an exposure of 15000 mm2/L.		
E — Growth of Aquatic Micro-organisms	Passed at an exposure of 6300 mm2/L with scaling factor of 0.42 applied.		
F — Cytotoxic Activity of Water Extract	Passed at an exposure of 15000 mm2/L.		
G - Mutagenic Activity of Water Extract	Passed at an exposure of 15000 mm2/L.		
H — Extraction of Metals	Passed at an exposure of 15000 mm2/L.		

Summary Comment : The sample was applied and cured by the submitting organisation.



PO Box 1751 Adelaide SA 5001 250 Victoria Square Adelaide SA 5000 Tel: 1300 653 366 Fax: 1300 883 171

Internet: www.awqc.com.au Email: awqc@sawater.com.au



FINAL REPORT

Report ID: 107478

CLAUSE 6.2 Taste of Water Extract

Sample Description The sample consisted of a panel with dimensions 25 mm x 40 mm providing a surface area

of 1000 mm2 per Litre. Extracts were prepared using 1000 mL volumes of 50 mg/L

hardness water.

Extraction Temperature 20°C ± 2°C.

Test Method Taste of Water Extract (Appendix C)

Test Information

Scaling Factor Not applied.

Results Not detected.

Evaluation The product passed the requirements of clause 6.2 when tested at an exposure of 1000

mm2 per Litre.

Number of Samples 2.

Test Comment Panellists detected stale tastes in the first dilution of the final (seventh) chlorinated extracts

when tested at an exposure of 6300 mm2/L. Test was repeated at 1000 mm2/L and no

tastes were detected.

Peter Christopoulos APPROVED SIGNATORY





Report ID: 107478

CLAUSE 6.3 Appearance of Water Extract

Sample Description The sample consisted of two glass slides each with a single side coated measuring 75 mm

x 100 mm giving an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of 50 mg/L hardness water.

Extraction Temperature 20°C ± 2°C.

Test Method Appearance of Water Extract (Appendix D)

Scaling Factor Not applied.

Results

	Test (- Blank)	Maximum Allowed	<u>Units</u>
Colour	<1	5	HU
Turbidity	0.1	0.5	NTU

Evaluation The product passed the requirements of clause 6.3 when tested at an exposure of 15000

mm2 per Litre.

Number of Samples 1.

Test Comment Not applicable.

Joanne Clark APPROVED SIGNATORY





Report ID: 107478

CLAUSE 6.4 Growth of Aquatic Micro-organisms

Sample Description The sample consisted of two glass slides each with a single side coated measuring 75 mm

x 100 mm giving an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of test water.

Test Method Growth of Aquatic Micro-organisms (Appendix E)

Inoculum The volume of the inoculum was 100 mL

Scaling Factor A scaling factor of 0.42 was applied.

Results

Mean Dissolved Oxygen Control 7.4 mg/L

Mean Dissolved Oxygen Difference Positive Reference 5.4 mg/L

Negative Reference <0.1 mg/L

Test 1.60 mg/L

Evaluation The product passed the requirements of clause 6.4 when tested at an exposure of 6300

mm2 per Litre with a scaling factor of 0.42 applied.

Number of Samples 1.

Test Comment The Mean Dissolved Oxygen Difference in the extracts exceeded the maximum allowable

concentration. A scaling factor of 0.42 was applied.

Stephanie Semczuk
APPROVED SIGNATORY



Tel: 1300 653 366 Fax: 1300 883 171

Internet: www.awqc.com.au Email: awqc@sawater.com.au



FINAL REPORT

Report ID: 107478

CLAUSE 6.5 Cytotoxic Activity of Water Extract

Sample Description The sample consisted of two glass slides each with a single side coated measuring 75 mm

x 100 mm giving an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of 50 mg/L hardness water.

Extraction Temperature 20°C ± 2°C.

Test Method Cytotoxic Activity of Water Extract (Appendix F)

Scaling Factor Not applied.

Results Non cytotoxic.

Evaluation The product passed the requirements of clause 6.5 when tested at an exposure of 15000

mm2 per Litre.

Number of Samples 1.

Test CommentThe test extracts and blank extracts were used to prepare nutrient growth medium and

subsequently used to grow a cell line (ATCC Number CCL 81) in the analysis. In addition

zinc sulphate (0.4 mmol) was used for the positive control in the analysis.

Brendon King APPROVED SIGNATORY





Report ID: 107478

CLAUSE 6.6 Mutagenic Activity of Water Extract

Sample Description The sample consisted of two glass slides each with a single side coated measuring 75 mm

x 100 mm giving an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of 50 mg/L hardness water.

Extraction Temperature 20°C ± 2°C.

Test Method Mutagenic Activity of Water Extract (Appendix G)

Scaling Factor Not applied.

Results

<u>Bacteria Strain</u> <u>Number of Revertants per Plate</u>

Salmonella typhimurium TA98 Mean ± Standard deviation	S9 -	Blank 34, 51, 47 44.0 ± 8.9	Sample Extract 45, 49, 44 46.0 ± 2.6	Positive Controls 1987, 2246, 1712 1981.7 ± 267.0	<u>NPD</u> (20μg)
Mean ± Standard deviation	+	45, 47, 38 43.3 ± 4.7	33, 40, 46 39.7 ± 6.5	1849, 2017, 1992 1952.7 ± 90.6	<u>2-AF</u> (20μg)
Salmonella typhimurium TA100 Mean ± Standard deviation	-	336, 327, 318 327.0 ± 9.0	314, 329, 282 308.3 ± 24.0	869, 849, 872 863.3 ± 12.5	<u>Azide</u> (1.0μg)
Mean ± Standard deviation	+	294, 296, 333 307.7 ± 22.0	302, 307, 290 299.7 ± 8.7	1503, 1601, 2462 1855.3 ± 527.7	<u>2-AF (</u> 20μg)
Salmonella typhimurium TA102 Mean ± Standard deviation	-	729, 698, 833 753.3 ± 70.7	709, 737, 721 722.3 ± 14.0	1876, 2000, 2004 1960.0 ± 72.8	<u>Mitomycin C(</u> 10μg)
Mean ± Standard deviation	+	712, 753, 1015 826.7 ± 164.4	828, 724, 1048 866.7 ± 165.4		

Comments S9 was used as a metabolic activator. NPD (4-nitro-o-phenylenediamine), Azide, and

Mitomycin C are specific positive controls for strains TA98, TA100 and TA102 respectively while 2 - AF (2-aminofluorene) when used in conjunction with S9 is a

positive control for both TA98 and TA100

Evaluation The product passed the requirements of clause 6.6 when tested at an exposure of 15000

mm2 per Litre.

Number of Samples 1.

Test Comment Not applicable.

Peter Christopoulos APPROVED SIGNATORY





Report ID: 107478

CLAUSE 6.7 **Extraction of Metals**

Sample Description The sample consisted of two glass slides each with a single side coated measuring 75 mm

x 100 mm giving an approximate surface area of 15000 mm2 per Litre. Extracts were

prepared using 1000 mL volumes of 50 mg/L hardness water.

Extraction Temperature 20°C ± 2°C.

Extraction of Metals (Appendix H) **Test Method**

Not applied. **Scaling Factor**

All methods used to determine concentrations of metals are based on those described in **Method of Analysis**

the 21st edition of Standard Methods for the Examination of Water and Wastewater published by the APHA, AWWA and WEF (2005). The methods have been adapted for

the instrumentation in use at the Australian Water Quality Centre.

Concentration of the metals described in Table 2 of the AS/NZS 4020:2005 are

determined as follows:

Antimony, Arsenic, Barium, Cadmium, Chromium, Copper, Lead, Mercury, Molybdenum,

Nickel, Selenium and Silver by Inductively Coupled Plasma Mass Spectrometry.

Results	Limit of Reporting mg/L	Blank mg/L	Test 1 mg/L	Test 2 mg/L	Max Allowed mg/L
Final Extract					
Antimony	0.0005	<0.0005	<0.0005	<0.0005	0.003
Arsenic	0.0003	< 0.0003	< 0.0003	< 0.0003	0.007
Barium	0.0005	<0.0005	<0.0005	< 0.0005	0.7
Cadmium	0.0005	<0.0001	< 0.0001	<0.0001	0.002
Chromium	0.0001	<0.0001	<0.0001	< 0.0001	0.05
Copper	0.0001	<0.0001	<0.0001	0.0003	2.0
Lead	0.0001	<0.0001	<0.0001	< 0.0001	0.01
Mercury	0.00003	0.00003	<0.00003	<0.00003	0.001
Molybdenum	0.0001	<0.0001	<0.0001	< 0.0001	0.05
Nickel	0.0001	<0.0001	<0.0001	0.0001	0.02
Selenium	0.0001	<0.0001	<0.0001	< 0.0001	0.01
Silver	0.00003	<0.00003	< 0.00003	<0.00003	0.1

Evaluation The product passed the requirements of clause 6.7 when tested at an exposure of 15000

mm2 per Litre.

Number of Samples

Not applicable. **Test Comment**

Dzung Bui

APPROVED SIGNATORY



Corporate Accreditation No.1115 Chemical and Biological Testing This document is issued in accordance with NATA's accreditation requirements.
Accredited for compliance with ISO/IEC 17025